

SUBMITTAL SHEET

Lateral Connection Products

For IPS & DIN Plastic Pipe



L90-Series Self-Restrained Bell Outlet Adapters

- L90-200... 2" IPS Spigot LAT Inlet x 2" IPS Self-Restrained Bell Outlet
- L90-250... 2" IPS Spigot LAT Inlet x 2.5" IPS Self-Restrained Bell Outlet
- L90-300... 2" IPS Spigot LAT Inlet x 3" IPS Self-Restrained Bell Outlet




2" L90 and L180-Series MPT Outlet Adapters

- L90-215 & L180-215... 2" IPS Spigot LAT Inlet x 1.5" MPT Outlet
- L90-220 & L180-220... 2" IPS Spigot LAT Inlet x 2" MPT Outlet
- L90-225... 2" IPS Spigot LAT Inlet x 2.5" MPT Outlet
- L90-230... 2" IPS Spigot LAT Inlet x 3" MPT Outlet



3" L90 and L180-Series MPT Outlet Adapters

- L180-320... 3" IPS Spigot Inlet x 2" MPT Outlet
- L90-325 & L180-325... 3" IPS Spigot Inlet x 2.5" MPT Outlet
- L90-330 & L180-330... 3" IPS Spigot Inlet x 3" MPT Outlet



2" LF90 and LF180-Series FPT Outlet Adapters

- LF90-215 & LF180-215... 2" IPS Spigot LAT Inlet x 1.5" FPT Outlet
- LF90-220 & LF180-220... 2" IPS Spigot LAT Inlet x 2" FPT Outlet



2" LFA-200 and LFA-300 FPT Outlet Adapters

- LFA-200... 2" IPS Spigot LAT Inlet x 2" FPT Outlet
- LFA-300... 2" IPS Spigot LAT Inlet x 3" FPT Outlet

MATERIAL:
HARDWARE:
PRESSURE RATING:
EPOXY COATING:
INSTALLATION:

Class 350 Ductile Iron per ASTM A-536, Grade 65-45-12, AWWA C153
Low Alloy Steel ANSI/AWWA C11/A21.11, Optional 304 & 316 stainless
350 PSI
ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 10-12 MIL
Per IPS & DIN Pipe Standards

Specification:

Lateral to mainline connection shall be made using Leemco Lateral Adapter. Adapter shall be made of ductile iron grade 65-45-12 (ASTM A-536). Epoxy Coating on interior & exterior surfaces of fittings shall be fusion bonded epoxy, 10-12 mil thickness. The epoxy coating shall pass 90-Day immersion tests per CSA Z245.20-98. Lateral Adapter shall be offered with self-restrained bell, MPT and FPT outlets. The Adapter inlet shall have a swivel base to orient the outlet to any 360 degree position for ease and stress free installation. Non self-restrained Lateral Adapter shall be equipped with tapped and plugged 1" side outlet. Adapter shall be used with Leemco saddle or tee. All Lateral Adapters shall be as manufactured by Leemco, Inc., U.S.A.

**Leemco has a large variety of Lateral Connection Adapters...
 Please refer to our IPS and DIN Price Lists for available Models and Sizes.**



Leemco, Inc.
 360 S. Mount Vernon
 Colton, CA. 92324
 Ph: (909) 422-0088 Fx: (909) 422-0086
 Web: www.leemco.com