

SUBMITTAL SHEET

Stainless Steel Saddles For IPS & METRIC PVC & HDPE Plastic Pipe



IPS MODELS

<u>MODEL NO.</u>	<u>DESCRIPTION</u>
RSST-215	2 x 1-1/2" FPT SS Saddle
RSST-215A	2 x 1-1/2" ACME SS Saddle
RSST-2515	2-1/2" x 1-1/2" FPT SS Saddle
RSST-2515A	2-1/2" x 1-1/2" ACME SS Saddle
RSST-315	3 x 1-1/2" FPT SS Saddle
RSST-315A	3 x 1-1/2" ACME SS Saddle

METRIC MODELS

<u>MODEL NO.</u>	<u>DESCRIPTION</u>
RSST-6315	63mm x 1-1/2" FPT SS Saddle
RSST-6315A	63mm x 1-1/2" ACME SS Saddle
RSST-6315B	63mm x 1-1/2" BSP SS Saddle
RSST-9015	90mm x 1-1/2" FPT SS Saddle
RSST-9015A	90mm x 1-1/2" ACME SS Saddle
RSST-9015B	90mm x 1-1/2" BSP SS Saddle

SADDLE SPECIFICATIONS... (includes all models)

SADDLE CONSTRUCTION
HARDWARE:
PRESSURE RATING:
GASKET:
SIZES:.....
SIZES:.....
INSTALLATION:

316 Stainless Steel per ASTM A240, Pacified for corrosion resistance
316 Stainless Steel per ASTM A240, Pacified for corrosion resistance
200 PSI
High grade EPDM rubber per ANSI/AWWA C111/A21.11
2", 2-1/2", 3" IPS Sizes (1-1/2" FPT or 1-1/2" ACME Outlets)
63mm & 90mm Sizes (1-1/2" FPT, ACME or BSP Outlets)
Per IPS & METRIC Pipe Standards

Specification:

Saddle construction shall be made of 316 stainless steel. Saddle shall have a round anti-rotation device that is built within the saddle and made to insert into a 1-1/2" cored out hole. Saddles shall have a built-on joint restraint system. Gasket seal shall be made of high grade EPDM rubber per ANSI/AWWA C111/A21.11. All saddles shall be manufactured by Leemco, Inc., U.S.A.



Leemco, Inc.
360 S. Mount Vernon
Colton, CA. 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
Web: www.leemco.com

Leemco has a large variety of Saddles & Accessories...
Please refer to our IPS and DIN Price Lists for available Models and Sizes.