

FPT & Lateral SS Range Saddles

For IPS & DIN Plastic Pipe

FPT Stainless Steel Strap Saddles



RSST and RSDT-Series Saddles...

Leemco saddles are made of durable ductile iron that have a fused epoxy finish specifically designed for high corrosive soils. All hardware and saddle straps are made of 304 stainless steel and the nuts are coated to prevent galling. The saddle gasket is constructed of high grade EPDM rubber for leak proof connections.

| Model No. | Description | Pipe Size | Outlet Size |
|-----------|--------------------------------------|------------------|-------------|
| RSST-304 | 3 x 2 FPT Saddle, Single SS Strap | 3" IPS or 90MM | 2" FPT |
| RSST-404 | 4 x 2 FPT Saddle, Single SS Strap | 4" IPS or 110MM | 2" FPT |
| RSST-604 | 6 x 2 FPT Saddle, Single SS Strap | 6" IPS or 160MM | 2" FPT |
| RSST-804 | 8 x 2 FPT Saddle, Single SS Strap | 8" IPS or 200MM | 2" FPT |
| RSST-1004 | 10 x 2 FPT Saddle, Single SS Strap | 10" IPS or 250MM | 2" FPT |
| RSST-1204 | 12 x 2 FPT Saddle, Single SS Strap | 12" IPS or 315MM | 2" FPT |
| RSST-963 | 90 x 63 FPT Saddle, Single SS Strap | 3" IPS or 90MM | 63MM DIN |
| RSST-1163 | 110 x 63 FPT Saddle, Single SS Strap | 4" IPS or 110MM | 63MM DIN |
| RSST-1663 | 160 x 63 FPT Saddle, Single SS Strap | 6" IPS or 160MM | 63MM DIN |
| RSST-2063 | 200 x 63 FPT Saddle, Single SS Strap | 8" IPS or 200MM | 63MM DIN |
| RSST-2563 | 250 x 63 FPT Saddle, Single SS Strap | 10" IPS or 250MM | 63MM DIN |
| RSST-3263 | 315 x 63 FPT Saddle, Single SS Strap | 12" IPS or 315MM | 63MM DIN |
| RSDT-304 | 3 x 2 FPT Saddle, Double SS Strap | 3" IPS or 90MM | 2" FPT |
| RSDT-404 | 4 x 2 FPT Saddle, Double SS Strap | 4" IPS or 110MM | 2" FPT |
| RSDT-604 | 6 x 2 FPT Saddle, Double SS Strap | 6" IPS or 160MM | 2" FPT |
| RSDT-804 | 8 x 2 FPT Saddle, Double SS Strap | 8" IPS or 200MM | 2" FPT |
| RSDT-1004 | 10 x 2 FPT Saddle, Double SS Strap | 10" IPS or 250MM | 2" FPT |
| RSDT-1006 | 10 x 3 FPT Saddle, Double SS Strap | 10" IPS or 250MM | 3" FPT |
| RSDT-1204 | 12 x 2 FPT Saddle, Double SS Strap | 12" IPS or 315MM | 2" FPT |
| RSDT-1206 | 12 x 3 FPT Saddle, Double SS Strap | 12" IPS or 315MM | 3" FPT |
| RSDT-1404 | 14 x 2 FPT Saddle, Double SS Strap | 14" DPS or 356MM | 2" FPT |
| RSDT-1406 | 14 x 3 FPT Saddle, Double SS Strap | 14" DPS or 356MM | 3" FPT |
| RSDT-1604 | 16 x 2 FPT Saddle, Double SS Strap | 16" DPS or 406MM | 2" FPT |
| RSDT-1606 | 16 x 3 FPT Saddle, Double SS Strap | 16" DPS or 406MM | 3" FPT |

**3/4", 1" & 1-1/2" FPT outlets are available
for an additional charge.**

Leemco has a large variety of Saddles and Accessories...
Please refer to our IPS and DIN Price Lists for available Models and Sizes.

Lateral Stainless Steel Strap Saddles



| Model No. | Description | Pipe Size | Outlet Size |
|-----------|------------------------------------|------------------|-------------|
| RSLs-300 | 3 x 2 LAT Saddle, Single SS Strap | 3" IPS or 90MM | 2" LAT BELL |
| RSLs-400 | 4 x 2 LAT Saddle, Single SS Strap | 4" IPS or 110MM | 2" LAT BELL |
| RSLs-600 | 6 x 2 LAT Saddle, Single SS Strap | 6" IPS or 160MM | 2" LAT BELL |
| RSLs-800 | 8 x 2 LAT Saddle, Single SS Strap | 8" IPS or 200MM | 2" LAT BELL |
| RSLs-1000 | 10 x 2 LAT Saddle, Single SS Strap | 10" IPS or 250MM | 2" LAT BELL |
| RSLs-1200 | 12 x 2 LAT Saddle, Single SS Strap | 12" IPS or 315MM | 2" LAT BELL |
| RDLS-300 | 3 x 2 LAT Saddle, Double SS Strap | 3" IPS or 90MM | 2" LAT BELL |
| RDLS-400 | 4 x 2 LAT Saddle, Double SS Strap | 4" IPS or 110MM | 2" LAT BELL |
| RDLS-600 | 6 x 2 LAT Saddle, Double SS Strap | 6" IPS or 160MM | 2" LAT BELL |
| RDLS-800 | 8 x 2 LAT Saddle, Double SS Strap | 8" IPS or 200MM | 2" LAT BELL |
| RDLS-1000 | 10 x 2 LAT Saddle, Double SS Strap | 10" IPS or 250MM | 2" LAT BELL |
| RDLS-1200 | 12 x 2 LAT Saddle, Double SS Strap | 12" IPS or 315MM | 2" LAT BELL |
| RDLS-1400 | 14 x 2 LAT Saddle, Double SS Strap | 14" DPS or 356MM | 2" LAT BELL |
| RDLS-1600 | 16 x 2 LAT Saddle, Double SS Strap | 16" DPS or 406MM | 2" LAT BELL |

RSLs and RDLS-Series Saddles...

Leemco saddles are made of durable ductile iron that have a fused epoxy finish specifically designed for high corrosive soils. All hardware and saddle straps are made of 304 stainless steel and the nuts are coated to prevent galling. All saddle gaskets are constructed of high grade EPDM rubber for leak proof connections. The 2" LAT Bell gasket outlet accepts Leemco Lateral Angle Valves and Lateral Accessories.



Picture of lateral valve inlet and lateral saddle bell outlet

SADDLE SPECIFICATIONS... (includes all models)

| | |
|-------------------------------|---|
| SADDLE BODIES: | Class 350 Ductile Iron per ASTM A-536, Grade 65-45-12, AWWA C153 |
| STAINLESS STRAP: | 304 Stainless Steel per ASTM A240, Pacified for corrosion resistance |
| HARDWARE: | 304 Stainless Steel per ASTM A240 |
| PRESSURE RATING: | 350 PSI |
| EPOXY COATING: | ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 10-12 MIL |
| GASKETS: | High grade EPDM rubber ANSI/AWWA C111/A21.11 |
| INSTALLATION: | Per IPS & DIN Pipe Standards |

Specification:

Saddle bodies shall be constructed of ductile iron per ASTM A-536, Grade 65-45-12, AWWA C153 standards. RSST, RSDT, RSLs & RDLS-Series straps and hardware shall be 304 stainless steel. Saddle gaskets shall be constructed of high grade EPDM rubber per ANSI/AWWA C111/A21.11 standards. Epoxy coating shall be 10-12MM thick to protect against corrosive soils. 2" LAT Bell outlet accepts Leemco lateral connections. All saddles shall be as manufactured by Leemco, Inc., U.S.A.



Leemco, Inc.
 360 S. Mount Vernon
 Colton, CA. 92324
 Ph: (909) 422-0088 Fx: (909) 422-0086
 Web: www.leemco.com