

DUCTILE IRON FITTINGS

DIN PRODUCTS - FLANGED FITTINGS



MATERIAL CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C515
EPOXY COATING ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 12-14 MIL
FLANGED ENDS CONFORM WITH ANSI B16.1 CLASS 125

IMPORTANT: Nut, bolt and gasket kits are sold separately. Please call Leemco for pricing.

SPECIFICATION

All flanged fittings shall meet AWWA C515 standards. Material shall be ductile iron per ASTM A536, Grade 65-45-12. Epoxy coating on all interior and exterior surfaces shall be fusion bonded epoxy, 12-14 mil thickness. The epoxy coating shall pass 90-Day immersion tests per CSA Z245.20-98. Flanges shall be class 125. All flanged fittings shall be manufactured by Leemco, Inc., U.S.A.

LEEMCO HAS A LARGE VARIETY OF DUCTILE IRON PRODUCTS.
 PLEASE VISIT OUR WEBSITE AT LEEMCO.COM



Leemco, Inc.
 360 S. Mount Vernon Ave.
 Colton, CA 92324
 Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com