## MAINLINE RESILIENT WEDGE GATE VALVES IPS PRODUCTS - LMV- & DLMV-SERIES FLANGED

## RESILIENT WEDGE MAINLINE GATE VALVES FOR IPS, DPS & DIN METRIC PLASTIC PIPE





LMV-FF (IPS & DPS) SERIES (FLANGE X FLANGE)				
MODEL #	FLANGE	FLANGE	SHROUD	
LMV-11FF	2"	2"	4" IPS	
LMV-22FF	2.5"	2.5"	4" IPS	
LMV-33FF	3"	3"	6" IPS	
LMV-44FF	4"	4"	6" IPS	
LMV-66FF	6"	6"	6" IPS	
LMV-88FF	8"	8"	6" IPS	
LMV-1010FF	10"	10"	6" IPS	
LMV-1212FF	12"	12"	6" IPS	
LMV-1414FF	14"	14"	6" IPS	
LMV-1616FF	16"	16"	6" IPS	
LMV-1818FF	18"	18"	6" IPS	
LMV-2020FF	20"	20"	6" IPS	
LMV-2424FF	24"	24"	6" IPS	

DLMV-FF (DIN) SERIES (FLANGE X FLANGE)				
MODEL #	FLANGE	FLANGE	SHROUD	
DLMV-99FF	90MM	90MM	6" IPS	
DLMV-1111FF	110MM	110MM	6" IPS	
DLMV-1616FF	160MM	160MM	6" IPS	
DLMV-2020FF	200MM	200MM	6" IPS	
DLMV-2525FF	250MM	250MM	6" IPS	
DLMV-3232FF	315MM	315MM	6" IPS	
DLMV-4040FF	400MM	400MM	6" IPS	
DLMV-4545FF	450MM	450MM	6" IPS	

## 250 PSI DUCTILE IRON BODY GATE VALVES

- Bolted Bonnet
- Non-Rising Stem
- Resilient Wedge
- Flanges Conform with ANSI B16.1 Class 125 (IPS & DPS)
- Conforms to AWWA C509 Standards
- 10-Year Warranty

AWWA C509 OR C515 STANDARDS

PRESSURE RATING ...... 250 PSI

**EPOXY COATING** ...... ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 12-14 MIL

**DEFLECTION** ...... 5 DEGREES

## **SPECIFICATION**

All mainline valves shall be resilient wedge and conform to AWWA C509 or C515 standards. Material shall be ductile iron per ASTM A536, Grade 65-45-12. Epoxy coating on all interior and exterior surfaces shall be fusion bonded epoxy, 12-14 mil thickness. The epoxy coating shall pass 90-Day immersion tests per CSA Z245.20-98. Flanged valve ends shall be class 125 for IPS and DPS sizes. Valves shall have a shroud around the 2" operating nut to accept IPS PVC sleeve which provides dirtfree access to actuate the valve. All mainline valves shall be manufactured by Leemco, Inc., U.S.A.

LEEMCO HAS A LARGE VARIETY OF VALVE ACCESSORIES.

PLEASE VISIT OUR WEBSITE AT LEEMCO.COM



Leemco, Inc. 360 S. Mount Vernon Ave. Colton, CA 92324 Ph: (909) 422-0088 Fx: (909) 422-0086

leemco.com