

MAINLINE RESILIENT WEDGE GATE VALVES

DPS (C900) PRODUCTS - LMV-SERIES

MECHANICAL JOINT MAINLINE GATE VALVES FOR IPS & DPS PLASTIC PIPE



| LMV-MM (IPS & DPS) SERIES (MJ X MJ) | | | |
|--|-----|-----|--------|
| MODEL # | MJ | MJ | SHROUD |
| LMV-33MM | 3" | 3" | 6" IPS |
| LMV-44MM | 4" | 4" | 6" IPS |
| LMV-66MM | 6" | 6" | 6" IPS |
| LMV-88MM | 8" | 8" | 6" IPS |
| LMV-1010MM | 10" | 10" | 6" IPS |
| LMV-1212MM | 12" | 12" | 6" IPS |
| LMV-1414MM | 14" | 14" | 6" IPS |
| LMV-1616MM | 16" | 16" | 6" IPS |
| LMV-1818MM | 18" | 18" | 6" IPS |
| LMV-2020MM | 20" | 20" | 6" IPS |
| LMV-2424MM | 24" | 24" | 6" IPS |

250 PSI DUCTILE IRON BODY GATE VALVES

- Bolted Bonnet
- Non-Rising Stem
- Resilient Wedge
- Conforms to AWWA C515 Standards
- Optional Round Wheel Handle
- 10-Year Warranty

| | |
|------------------------------|---|
| MATERIAL | CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C515 |
| PRESSURE RATING | 250 PSI |
| EPOXY COATING | AWWA C550, NSF 61 & CSA Z245.20-98, 12-14 MIL |
| WEDGE | DUCTILE IRON ASTM A536, EPDM RUBBER, ASTM D429 |
| GASKETS/O-RINGS | HIGH GRADE EPDM RUBBER |
| INSTALLATION | PER IPS & DPS PIPE STANDARDS |

SPECIFICATION

All mainline valves shall be resilient wedge and conform to AWWA C515 standards. Material shall be ductile iron per ASTM A536, Grade 65-45-12. Epoxy coating on all interior and exterior surfaces shall be fusion bonded epoxy, 12-14 mil thickness. The epoxy coating shall pass 90-Day immersion tests per CSA Z245.20-98. Valves shall have a shroud around the 2" operating nut to accept IPS PVC sleeve which provides dirt-free access to actuate the valve. All mainline valves shall be manufactured by Leemco, Inc., U.S.A.

MAINLINE RESILIENT WEDGE GATE VALVES
CAT. D

LEEMCO HAS A LARGE VARIETY OF VALVE ACCESSORIES.
PLEASE VISIT OUR WEBSITE AT LEEMCO.COM



Leemco, Inc.
360 S. Mount Vernon Ave.
Colton, CA 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com