

MAINLINE RESILIENT WEDGE GATE VALVES

IPS PRODUCTS - LMV-SERIES

MECHANICAL JOINT MAINLINE GATE VALVES FOR IPS & DPS PLASTIC PIPE



LMV-MM (IPS & DPS) SERIES (MJ X MJ)			
MODEL #	MJ	MJ	SHROUD
LMV-33MM	3"	3"	6" IPS
LMV-44MM	4"	4"	6" IPS
LMV-66MM	6"	6"	6" IPS
LMV-88MM	8"	8"	6" IPS
LMV-1010MM	10"	10"	6" IPS
LMV-1212MM	12"	12"	6" IPS
LMV-1414MM	14"	14"	6" IPS
LMV-1616MM	16"	16"	6" IPS
LMV-1818MM	18"	18"	6" IPS
LMV-2020MM	20"	20"	6" IPS
LMV-2424MM	24"	24"	6" IPS

250 PSI DUCTILE IRON BODY GATE VALVES

- Bolted Bonnet
- Non-Rising Stem
- Resilient Wedge
- Conforms to AWWA C515 Standards
- Optional Round Wheel Handle
- 10-Year Warranty

MATERIAL	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C515
PRESSURE RATING	250 PSI
EPOXY COATING	AWWA C550, NSF 61 & CSA Z245.20-98, 12-14 MIL
WEDGE	DUCTILE IRON ASTM A536, EPDM RUBBER, ASTM D429
GASKETS/O-RINGS	HIGH GRADE EPDM RUBBER
INSTALLATION	PER IPS & DPS PIPE STANDARDS

SPECIFICATION

All mainline valves shall be resilient wedge and conform to AWWA C515 standards. Material shall be ductile iron per ASTM A536, Grade 65-45-12. Epoxy coating on all interior and exterior surfaces shall be fusion bonded epoxy, 12-14 mil thickness. The epoxy coating shall pass 90-Day immersion tests per CSA Z245.20-98. Valves shall have a shroud around the 2" operating nut to accept IPS PVC sleeve which provides dirt-free access to actuate the valve. All mainline valves shall be manufactured by Leemco, Inc., U.S.A.



Leemco, Inc.
360 S. Mount Vernon Ave.
Colton, CA 92324
Ph: (909) 422-0088 Fx: (909) 422-0086
leemco.com

LEEMCO HAS A LARGE VARIETY OF VALVE ACCESSORIES.
PLEASE VISIT OUR WEBSITE AT LEEMCO.COM

CAT. D
MAINLINE RESILIENT
WEDGE GATE VALVES