

LATERAL CONNECTION SYSTEM

IPS PRODUCTS - LV-SERIES ANGLE VALVES



LATERAL TEE

- LT-200T (2")
- LT-300T (3")
- LT-400T (4")
- LT-600T (6")
- LT-800T (8")
- LT-1000T (10")
- LT-1200T (12")

RSLS-SERIES SINGLE SS STRAP SADDLE

- RSLS-300 (3")
- RSLS-400 (4")
- RSLS-600 (6")
- RSLS-800 (8")
- RSLS-1000 (10")
- RSLS-1200 (12")

RDLS-SERIES DOUBLE SS STRAP SADDLE

- RDLS-300 (3")
- RDLS-400 (4")
- RDLS-600 (6")
- RDLS-800 (8")
- RDLS-1000 (10")
- RDLS-1200 (12")

LX-SERIES EXTENSIONS

- LX-6 (6")
- LX-12 (12")

LMN-SERIES (SPIGOT X MPT) OUTLET ADAPTER

- LMN-10 (1")
- LMN-12 (1.25")
- LMN-15 (1.5")
- LMN-20 (2")
- LMN-25 (2.5")
- LMN-30 (3")
- LMN-31 (3" SPIGOT X 2" MPT)

INLET ADAPTERS

- LMA-200 (2" MPT X BELL)
- FMA-200 (2" FPT X BELL)
- LFA-200 (2" SPIGOT X 2" FPT)
- LFA-300 (2" SPIGOT X 3" FPT)
- LMA-200S (2" MPT X BELL) (stainless steel)

MATERIAL	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C153
PRESSURE RATING	250 PSI
EPOXY COATING	ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 10-12 MIL
HARDWARE	304 STAINLESS STEEL, OPTIONAL 316 STAINLESS STEEL
GASKETS	HIGH GRADE EPDM RUBBER ANSI/AWWA C111/A21.11, RIB-ENFORCED DESIGN
INSTALLATION	PER HDPE PIPE STANDARDS

SPECIFICATION

All lateral connection products shall be made with ductile iron per ASTM A536, Grade 65-45-12. All exterior and interior surfaces shall be fusion bonded epoxy coating, 10-12 mil thickness. All lateral connection products shall be manufactured by Leemco, Inc., U.S.A.

TORQUE RATING FOR SADDLES: 20-25 LB

LEEMCO HAS A LARGE VARIETY OF FITTINGS AND VALVE ACCESSORIES.

PLEASE REFER TO OUR IPS PRICE LISTS FOR AVAILABLE MODELS AND SIZES.



Leemco, Inc.
 360 S. Mount Vernon Ave.
 Colton, CA 92324
 Ph: (909) 422-0088 Fx: (909) 422-0086
 leemco.com