

**DUCTILE IRON VALVE BOX (FOR QUICK COUPLING VALVES)  
DIN PRODUCTS - QUICK COUPLING VALVE CONNECTION**

CAT. A  
DUCTILE IRON VALVE BOX



<b>MODEL #</b> .....	LVB-12R
<b>MATERIAL</b> .....	CLASS 350 DUCTILE IRON PER ASTM A536, GRADE 65-45-12, AWWA C153
<b>PRESSURE RATING</b> .....	250 PSI
<b>EPOXY COATING</b> .....	ANSI/AWWA C116/A21.16-09, NSF 61 & CSA Z245.20-98, 12-14 MIL
<b>QCV STABILIZER</b> .....	304 STAINLESS STEEL PLATE
<b>BALL VALVE</b> .....	1" FPT, 304 STAINLESS STEEL, FULL PORT, 1000 PSI, WATER, OIL & GAS (WOG)
<b>QCV ASSEMBLY</b> .....	1" MPT, 304 STAINLESS STEEL
<b>LID REMOVAL TOOL</b> .....	304 STAINLESS STEEL
<b>WEIGHT</b> .....	75 LB; 34 KG

**SPECIFICATION**

All quick coupling valves will be installed inside the Leemco LVB-12R ductile iron valve box. Valve box body and lid is constructed of Class 350 ductile iron per ASTM A536, Grade 65-45-12, AWWA C153 standards. The ductile iron body and lid have a FBE (fusion-bonded-epoxy) coating, ANSI/AWWA C116/A21.16-09, NSF 61 and CSA Z245.20-98, 12-14 MIL. All connection fittings, ball valve and lid removal tool are constructed of 304 stainless steel. All valve boxes shall be manufactured by Leemco, Inc. U.S.A.

LEEMCO HAS A LARGE VARIETY OF FITTINGS AND VALVE ACCESSORIES. PLEASE VISIT OUR WEBSITE AT LEEMCO.COM



Leemco, Inc.  
360 S. Mount Vernon Ave.  
Colton, CA 92324  
Ph: (909) 422-0088 Fx: (909) 422-0086  
leemco.com